

Embedded Computing Client (ECC)- WINDOWS



PROFILE

The most advance range of customized Thin Clients for all Verticals. ECC-Windows is a highly efficient and powerful thin client for both local computing, virtual desktop environments, web enabled and ERP. It has a Windows style desktop.

Advantages Snap Shot

- Cost-effective
- High reliability, No moving parts
- Low power consumption
- Low CO2 emission
- High ROI
- Virus Free
- Enhanced Security
- Highly Customizable in terms of software as well as hardware , can provide support for legacy ports



CONNECTIVITY & FEATURES

- | | |
|----------------------|-------------------|
| Front Panel - | • HDMI (optional) |
| • Power Button | • VGA |
| • LED Indicators | • RJ-45 |
| Side Panel - | • Mic-in |
| • USB 2.0 Ports | • Speaker-out |
| • Mic-in | • USB 3.0 |
| • Speaker-out | • USB 2.0 |
| Back Panel - | • PS2 |
| • Serial Ports | • DC-in |
| • Parallel Port | |

- Internet Explorer 11.0
- Support for EWF & FBWF Manager
- Multi-user / Single user login support.
- Time synchronization option from central server
- DHCP, DNS & WINS Support.
- Support for Telnet
- Mozilla Firefox (Optional)
- Chrome Browser (Optional)
- PDF reader, Open office, Flash Player, JVM,
- Calculator
- Dual Flash (optional)

BREEZE INNOVATIONS Pvt. LTD.



SPECIFICATION

SYSTEM

Processor	Intel Dual-Core/Quad core 1.8 Ghz or above
Available Operating System	Windows WES & Win 10 IOT Supported
Protocol Support	Microsoft RDP

MEMORY

RAM (DDR3)	2GB (Max up to 4/8GB)
Storage (Flash)	8GB (up to 128GB or optional HDD & secondary Flash)

DISPLAY

Port	HDMI x 1 (optional) & VGA x 1
Resolution	1920x1200 (VGA) 1920x1200 (HDMI)-optional
Color Depth	32 bits
Dual Display	Supported

NETWORK

LAN	x1 (10/100/1000 Base-T Fast Ethernet, RJ-45)
WLAN	Optional

I/O PERIPHERAL INTERFACE

USB 2.0	x 5 (front x 2, rear x 4) or above
USB 3.0	x 1 - optional
Serial Port	x 1 (Plus one additional header)
Parallel port	x 1 -Optional
PS/2	x 1 or above

AUDIO

Ports	Front: Speaker-out x 1 , Mic-in x 1, (1/8-inch mini jack)
-------	---

DIMENSION

Device	212mm x 62.8mm x 210.6mm
Packaging	110mm x 312mm x 307mm
Net Weight	1.6 kg nett

POWER

Adapter	100-240V AC, 50Hz, 12V/5A DC
Power Consumption	< 60w

MOUNTING

Stand	Vertical feet standard
-------	------------------------

ENVIRONMENT

Cooling	Fan-less Convection
Operation Temperature	0°C to 40°C
Relative Humidity	30% to 90% non-condensing

The information contained herein is subject to change without notice. Breeze shall not be liable for technical or editorial errors or omissions contained herein.

ISO 9001-2008 Certified

Website: www.breezeinnovations.com

e-mail: breeze@breezeinnovations.com



Call Toll Free 1800 274 2211 or visit our website www.breezeinnovations.com for product recycling